



GYD970L SERIES

LED Explosion Proof Street Light

- ใช้ไดร์เวอร์และเบ็ดซีป led คุณภาพสูง
- ผลิตจากอลูมิเนียมอัลลอยคุณภาพสูง แข็งแรง และทนทาน
- ป้องกันการกระแทกด้วยกระจกนิรภัย
- ผ่านการรับรองมาตรฐานการกันระเบิดตามหลักสากล
- กันน้ำกันฝุ่น IP66




กระทรวงพลังงาน
MINISTRY OF ENERGY

SPECIFICATIONS

Model	GYD970L1	GYD970L2	GYD970L3	GYD970L4
Watt	50W	100W	150W/200W	240W
Ex-mark for Gas	Ex II 2 G Ex db eb IIC T6 Gb			
Ex-mark for Dust	Ex II 2 D Ex tb IIIC T80°C Db			
Classification	Zone 1,2 & Zone 21,22			
Input Voltage	100-277V/50-60Hz			
Color Temperature	3500K-6500K			
Luminous Flux	6,500lm	13,000lm	19,500lm/26,000lm	31,200lm
Light Efficiency	130 lm/W			
Operating Temperature	-40°C to +50°C			
Power factor	>0.95			
Beam Angle	120° (60°, 90° is optional)			
CRI	≥70			
Surge Protection	4kV			
Life Time	>50,000 hrs			
IP Rating	IP66			
Warranty	1 years			
Dimension (AxBxC)	560x180x55 mm	635x240x55 mm	730x275x55 mm	820x330x55 mm
Net Weight	7.2 kg	9.8 kg	12.3 kg	16 kg
Mounting Styles	Pole			
Conduit Entries	G 3/4"			
Material	Aluminium ,Tempered glass			

Photometric



Accessories

Pole Mount

INSTALLATION



DIMENSIONS (mm)

