



## ■ Features:

- Zone 1&2, Zone 21&22
- Instant on crisp white light output
- High efficiency drivers and LEDs provide, low cost operation in harsh and heavy industrial applications
- Isolated LED compartment reduces temperature within driver housing
- Dense cooling fins design enhances airflow for greater heat dissipation

## Technical Parameters

| Type                                                                                              | SL-EXP-GYD2106                            | SL-EXP-GYD2107 | SL-EXP-GYD2108 |
|---------------------------------------------------------------------------------------------------|-------------------------------------------|----------------|----------------|
| European (ATEX)  | CE 1282 Ex II 2G Ex d IIC Gb              |                |                |
| Gas and Dust                                                                                      | CE 1282 Ex II 2D Ex tb Db                 |                |                |
| Input voltage                                                                                     | 100-240VAC, 50-60Hz                       |                |                |
| Power consumption [W]                                                                             | 20~50                                     | 60~100         | 120~240        |
| Luminaire efficiency [Lm/W]                                                                       | 100-120                                   |                |                |
| Degree of protection                                                                              | IP66                                      |                |                |
| Size [mm]                                                                                         | 210*210*250                               | 260*260*270    | 320*320*310    |
| Weight [kg]                                                                                       | 4.5                                       | 5.0            | 9.1            |
| Mounting Styles                                                                                   | Pendant; Ceiling; Wall Bracket; Stanchion |                |                |

## Dimension & Installation [mm]

