



150W

Product Specifications (MASTER-9 Series)

Specification	SL-FLM50-9	SL-FLM100-9	SL-FLM150-9	SL-FLM200-9	SL-FLM240-9	SL-FLM300-9	SL-FLM400-9	SL-FLM500-9		
Power Watt	50W	100W	150W	200W	240W	300W	400W	500W		
LED Brand	LUMILEDS									
Input Voltage	AC 100-277V/50-60Hz									
Color Temperature	3000K-6000K									
Luminous Flux	7,500 lm	15,000 lm	22,500 lm	30,000 lm	36,000 lm	45,000 lm	58,000 lm	72,500 lm		
Light Efficiency	150 lm/W									
Operating Temperature	-30°C to +55°C									
Power factor	>0.95									
Beam Angle	30°/60°/90°/120°/Type II/Type III						55x125°/60°/26x60°(tilt10°)/25°			
CRI	>70									
Surge Protection	10-20kV									
IP Rating	IP66									
IK Rating	IK08									
Life Time	>100,000 hrs									
Dimension	292x245x55 mm	353x287x65 mm	392x319x70 mm	447x359x75mm	495x419x75mm		624.4x407x88.9 mm			
Net Weight	1.9 kg	2.8 kg	3.9 kg	5.2 kg	6.3 kg	6.4 kg	9.2 kg	10.1 kg		
Material	Aluminum, PC									
Mounting Styles	Bracket Mounting, Pole Mounting									

Dimension

50W	100W	150W	200W	240W,300W	